Series **AR600**

Electronics
- **High Power**

Electromechanical
Custom

ACTRONIC

Tree-phase filter without common neutral line. This series is realized with a current range from 10A up to 200A

Filtro rete trifase senza neutro in modo comune. Questa serie viene realizzata da 10A fino a correnti di 200A

Technical Specifications:

Manufacture
Metal case, internal components sealed with self-extinguishing resin Vo

Connections
Faston 6.3x0.8mm (≤ 20A),
flexible leads or Screws M5/M8/M10/M12
Ground terminal connected to case

Caratteristiche tecniche:

Costruzione
Custodia metallica, componenti interni sigillati con resina autoestinguente Vo

Terminali
Faston 6.3x0.8mm (≤ 20A),
cavi flessibili o viti da M5/M8/M10/M12
Terminale di terra collegato alla custodia

Electrical specifications:

Rated voltage (Vr)	250/460Vac at 50/60Hz
Rated current (Ir)*	refferred to room temp.= 40°C
Voltage test (2s.)	line to ground 3000 Vdc or 1800 Vac line to line 1700 Vdc
Climatic category	HPF (25/085/21) -25°C to +85°C

Caratteristiche elettriche:

Tensione nominale (Vr)	250/460Vac a 50/60Hz
Corrente nominale (Ir) *	riferita ad una temp.di 40°C
Tensione di prova (2s.)	linea e massa 3000 Vdc o 1800 Vac linea e linea 1700 Vdc
Categoria climatica	HPF (25/085/21) -25°C to +85°C

Circuit diagram



Code	IR(A)*	L1(mH)	R=MΩ	Case
AR600.10A	3 x 10	1.5	10	B
AR600.16A	3 x 16	1.5	4.5	B
AR600.30A	3 x 30	1.5	3	F6
AR600.50A	3 x 50	1.5	2.5	F7
AR600.80A	3 x 80	0.9	1.5	F7
AR600.100A	3 x 100	0.6	1	F7
AR600.120A	3x 120	0.6	0.8	F7
AR600.150A	3 x 150	0.6	1.7	F40B
AR600.200A	3 x 200	0.6	0.4	F40B

Dimensions:

See the page Dimensions
Consultare la pagina Dimensioni

APPROVALS

CE RoHS COMPLIANT